

C1631...14MS... | 正齿轮系列 Spur Gearbox Series

应用领域：医疗器械、精密仪器、工业设备等领域。

Applications: medical equipment, scientific instruments, industrial equipment, etc.

工作温度范围 | Operating temperature range: -10~+80°C

配合电机类型 Matched Motor Type	齿轮工艺 Gear Processing Technology	齿轮组输出轴承 Gearbox Output Bearing
☐ 无刷电机 BLDC motor ☐ 空心杯电机 Coreless motor ☒ 铁芯电机 Cored motor ☐ 步进电机 Step motor	☒ 金属加工 Metal CNC ☒ 金属注塑 Metal injection ☐ 粉末冶金 Powder metallurgy ☐ 塑胶注塑 Plastic injection	☒ 含油轴承 Sleeve bearing ☐ 滚珠轴承 Ball bearing

电机主要技术指标 | Motor Characteristics


C1620F13-0032

1 电压	Voltage	V	6.0
2 端电阻	Terminal resistance	Ω	10.3
3 空载转速	No-load speed	rpm	11700
4 空载电流	No-load current	mA	51
5 堵转转矩	Stall torque	mNm	2.36
6 堵转电流	Stall current	mA	580
7 额定转矩	Nominal torque	mNm	2.10
8 额定转速	Nominal speed	rpm	1305
9 额定电流	Nominal current	mA	520
10 最大输出功率	Max. output power	W	0.73
11 最大效率	Max. efficiency	%	50
12 反电势常数	Back-EMF constant	mV/rpm	0.47
13 转矩常数	Torque constant	mNm/A	4.47
14 转速 / 转矩斜率	Speed/torque gradient	rpm/mNm	4950
15 转子惯量	Rotor inertia	gcm^2	0.5
16 重量	Weight	g	11

齿轮组主要技术指标 (金属加工) | Gearbox Characteristics (Metal CNC)

齿轮级数 Gearbox stages	减速比 Reduction ratio	最大额定转矩 Max. rated torque	瞬间允许转矩 Max. momentary torque	长度 Length (L)
		mNm	mNm	mm
2	63	60	180	12
2	115, 130, 150, 180	70	210	12
4	210, 250, 260	80	240	12
4	300, 350	100	300	12
--	--	--	--	--
--	--	--	--	--
--	--	--	--	--

外观图 | Outline Drawing



规格如有变更, 恕不另行通知
Specification subject to change without notice