

3257N9C2B | 碳刷 Graphite Brush

应用领域：医疗、保健、汽车、机器人、工业自动化等精密驱动领域。

Applications: precision drives in medical equipment and devices, healthcare products, automotive, robotics, and industrial automation.

主要技术指标 | Characteristics

			01-54-12.0	02-64-24.0	08-74-24.0
1 电压	Voltage	V	12.0	24.0	24.0
2 转子电阻	Rotor Resistance	Ω	0.44	2.3	1.84
3 空载转速	No-load speed	rpm	5440	6400	7400
4 空载电流	No-load current	mA	150	100	100
5 堵转转矩	Stall torque	mNm	568.1	366.4	397.7
6 堵转电流	Stall current	mA	27270	10430	13040
7 额定转矩	Nominal torque	mNm	45.5	38.5	31.8
8 额定转速	Nominal speed	rpm	5000	5730	6810
9 额定电流	Nominal current	mA	2320	1190	1130
10 最大输出功率	Max. output power	W	81	61	77
11 最大效率	Max. efficiency	%	86	81	83
12 反电势常数	Back-EMF constant	mV/rpm	2.2	3.7	3.2
13 转矩常数	Torque constant	mNm/A	20.9	35.5	30.7
14 转速 / 转矩斜率	Speed/torque gradient	rpm/mNm	9.6	17.5	18.6
15 转子惯量	Rotor inertia	gcm ²	42	42	42
16 重量	Weight	g	230	230	230
17 热阻 (机壳 - 环境)	Thermal resistance housing-ambient	K/W		7.57	
18 热阻 (线圈 - 机壳)	Thermal resistance winding-housing	K/W		4.05	
19 热时常数 (电机)	Thermal time constant motor	s		725	
20 热时常数 (线圈)	Thermal time constant winding	s		540	
21 工作温度范围	Operating temperature range	°C		-20~+120	
22 绕组耐温等级	Thermal class of winding	°C		155	
23 轴向间隙	Axial play	mm		0.02~0.15	
24 径向间隙	Radial play	mm		0.025	
25 动态轴向载荷	Axial load dynamic	N		5.6	
26 静态轴向载荷	Axial load static	N		110	
27 径向载荷 (距安装面 3mm)	Radial load at 3 mm from mounting face	N		30	
28 极对数	No. of pole pairs			1	
29 轴承	Bearings			2 枚滚动轴承/2 ball bearings	
30 换向结构	Commutator			贵金属 9 相/metal 9 segments	
31 防护等级	Protection class			IP 20	

★可选参数 Options: 导线长度 Lead wires length 轴长 Shaft length 性能 Special coils

齿轮箱 Gearheads 编码器 Encoder

外观图 | Outline Drawing

