

C12**...14MS... | 正齿轮系列 Spur Gearbox Series

应用领域：医疗器械、精密仪器、工业设备等领域。

Applications: medical equipment, scientific instruments, industrial equipment, etc.

工作温度范围 | Operating temperature range: -10~+80°C

配合电机类型 Matched Motor Type	齿轮工艺 Gear Processing Technology	齿轮组输出轴承 Gearbox Output Bearing
☐ 无刷电机 BLDC motor ☐ 空心杯电机 Coreless motor ☒ 铁芯电机 Cored motor ☐ 步进电机 Step motor	☒ 金属加工 Metal CNC ☒ 金属注塑 Metal injection ☐ 粉末冶金 Powder metallurgy ☐ 塑胶注塑 Plastic injection	☒ 含油轴承 Sleeve bearing ☐ 滚珠轴承 Ball bearing


电机主要技术指标 | Motor Characteristics

			C1215F33-0128	C1215F13-0462
1 电压	Voltage	V	6.0	1.5
2 端电阻	Terminal resistance	Ω	40.0	1.2
3 空载转速	No-load speed	rpm	8300	11800
4 空载电流	No-load current	mA	25	100
5 堵转转矩	Stall torque	mNm	0.72	1.28
6 堵转电流	Stall current	mA	150	1250
7 额定转矩	Nominal torque	mNm	0.35	0.60
8 额定转速	Nominal speed	rpm	4260	6287
9 额定电流	Nominal current	mA	90	640
10 最大输出功率	Max. output power	W	0.16	0.40
11 最大效率	Max. efficiency	%	35	51
12 反电势常数	Back-EMF constant	mV/rpm	0.60	0.12
13 转矩常数	Torque constant	mNm/A	5.75	1.12
14 转速 / 转矩斜率	Speed/torque gradient	rpm/mNm	11543	9188
15 转子惯量	Rotor inertia	gcm ²	0.3	0.3
16 重量	Weight	g	5.4	5.4

齿轮组主要技术指标 (金属加工) | Gearbox Characteristics (Metal CNC)

齿轮级数 Gearbox stages	减速比 Reduction ratio	最大额定转矩 Max. rated torque	瞬间允许转矩 Max. momentary torque	长度 Length (L)
		mNm	mNm	mm
2	3, 5, 10	20	60	9
4	17, 20, 30, 36	30	90	9
4	50, 63	40	120	9
5	100, 150, 210	60	180	9
5	250, 298, 380	80	240	9
7	372, 625, 1000	100	300	12
--	--	--	--	--

外观图 | Outline Drawing



规格如有变更，恕不另行通知
Specification subject to change without notice